

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### Oktan-Booster 206 - 300 ml

Revision date: 13.01.2026

Product code: 1105024

Page 1 of 13

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1. Product identifier

Oktan-Booster 206 - 300 ml

### 1.2. Relevant identified uses of the substance or mixture and uses advised against

#### Use of the substance/mixture

Additive

### 1.3. Details of the supplier of the safety data sheet

Company name: parts-center ag  
 Street: Heiligwies 16a  
 Place: LI Balzers  
 Post-office box: 120  
 LI-9496 Balzers  
 Telephone: +41 32 512 13 21  
 E-mail: info@parts-center.ch

**1.4. Emergency telephone number:** 1774 / +356 2559 4600

## SECTION 2: Hazards identification

### 2.1. Classification of the substance or mixture

#### Regulation (EC) No 1272/2008

Flam. Liq. 2; H225  
 Skin Irrit. 2; H315  
 STOT SE 3; H336  
 Asp. Tox. 1; H304  
 Aquatic Chronic 3; H412

Full text of hazard statements: see SECTION 16.

### 2.2. Label elements

#### Regulation (EC) No 1272/2008

#### Hazard components for labelling

Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, <2% aromatics

**Signal word:** Danger

#### Pictograms:



#### Hazard statements

H225 Highly flammable liquid and vapour.  
 H304 May be fatal if swallowed and enters airways.  
 H315 Causes skin irritation.  
 H336 May cause drowsiness or dizziness.  
 H412 Harmful to aquatic life with long lasting effects.

#### Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
 P261 Avoid breathing vapours.  
 P271 Use only outdoors or in a well-ventilated area.  
 P273 Avoid release to the environment.

# Safety Data Sheet

according to Regulation (EC) No 1907/2006

## Oktan-Booster 206 - 300 ml

Revision date: 13.01.2026

Product code: 1105024

Page 2 of 13

P280	Wear protective gloves.
P301+P310	IF SWALLOWED: Immediately call a POISON CENTER/doctor.
P331	Do NOT induce vomiting.
P303+P361+P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.
P332+P313	If skin irritation occurs: Get medical advice/attention.
P304+P312	IF INHALED: Call a POISON CENTER or doctor/physician if you feel unwell.

### SECTION 3: Composition/information on ingredients

#### 3.2. Mixtures

##### Relevant ingredients

CAS No	Chemical name	Quantity		
	EC No	Index No	REACH No	
	Classification (Regulation (EC) No 1272/2008)			
64742-48-9	Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, <2% aromatics			50 - < 100 %
	927-241-2		01-2119471843-32	
	Flam. Liq. 3, STOT SE 3, Asp. Tox. 1, Aquatic Chronic 3; H226 H336 H304 H412 EUH066			
1634-04-4	tert-butyl methyl ether; MTBE; 2-methoxy-2-methylpropane			25 - < 50 %
	216-653-1	603-181-00-X		
	Flam. Liq. 2, Skin Irrit. 2; H225 H315			
68608-26-4	Sulfonic acids, petroleum, sodium salts			3 - < 5 %
	271-781-5		01-2119527859-22	
	Eye Irrit. 2; H319			
67-56-1	methanol			0.1 - < 1 %
	200-659-6	603-001-00-X	01-2119433307-44	
	Flam. Liq. 2, Acute Tox. 3, Acute Tox. 3, Acute Tox. 3, STOT SE 1; H225 H331 H311 H301 H370			

Full text of H and EUH statements: see section 16.

##### Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity
	Specific Conc. Limits, M-factors and ATE		
64742-48-9	927-241-2	Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, <2% aromatics	50 - < 100 %
	inhalation: LC50 = > 4951 mg/l (vapours); dermal: LD50 = > 5000 mg/kg; oral: LD50 = > 5000 mg/kg		
1634-04-4	216-653-1	tert-butyl methyl ether; MTBE; 2-methoxy-2-methylpropane	25 - < 50 %
	inhalation: LC50 = 85 mg/l (vapours); dermal: LD50 = > 2000 mg/kg; oral: LD50 = 3866 mg/kg		
68608-26-4	271-781-5	Sulfonic acids, petroleum, sodium salts	3 - < 5 %
	inhalation: LC50 = >5 mg/l (dusts or mists); dermal: LD50 = >5000 mg/kg; oral: LD50 = >5000 mg/kg		
67-56-1	200-659-6	methanol	0.1 - < 1 %
	inhalation: LC50 = 128,2 mg/l (vapours); inhalation: ATE = 0,5 mg/l (dusts or mists); dermal: LD50 = 17100 mg/kg; oral: LD50 = 6000 mg/kg STOT SE 1; H370: >= 10 - 100 STOT SE 2; H371: >= 3 - < 10		

### SECTION 4: First aid measures

#### 4.1. Description of first aid measures

##### General information

First aider: Pay attention to self-protection! Remove persons to safety. Never give anything by mouth to an unconscious person or a person with cramps.

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### Oktan-Booster 206 - 300 ml

Revision date: 13.01.2026

Product code: 1105024

Page 3 of 13

#### **After inhalation**

Remove person to fresh air and keep comfortable for breathing. In all cases of doubt, or when symptoms persist, seek medical advice.

#### **After contact with skin**

Wash with plenty of water and soap. Take off immediately all contaminated clothing and wash it before reuse. In all cases of doubt, or when symptoms persist, seek medical advice.

#### **After contact with eyes**

Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. In case of troubles or persistent symptoms, consult an ophthalmologist.

#### **After ingestion**

Do NOT induce vomiting. Observe risk of aspiration if vomiting occurs. Call a physician in any case!

#### **4.2. Most important symptoms and effects, both acute and delayed**

Headache, nausea, dizziness, fatigue, skin irritation

#### **4.3. Indication of any immediate medical attention and special treatment needed**

Treat symptomatically. Call a POISON CENTER. Symptoms can occur only after several hours.

### **SECTION 5: Firefighting measures**

#### **5.1. Extinguishing media**

##### **Suitable extinguishing media**

Water mist. Foam. Carbon dioxide (CO<sub>2</sub>). Extinguishing powder.

##### **Unsuitable extinguishing media**

Full water jet

#### **5.2. Special hazards arising from the substance or mixture**

Incomplete combustion and thermolysis gases of different toxicity can occur. In the case of hydrocarbonaceous products such as CO, CO<sub>2</sub>, aldehydes and soot. These can be very dangerous if they are inhaled in high concentrations or in enclosed spaces.

#### **5.3. Advice for firefighters**

In case of fire and/or explosion do not breathe fumes. Move undamaged containers from immediate hazard area if it can be done safely. In case of fire: Wear self-contained breathing apparatus.

#### **Additional information**

Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

### **SECTION 6: Accidental release measures**

#### **6.1. Personal precautions, protective equipment and emergency procedures**

##### **General advice**

Wear breathing apparatus if exposed to vapours/dusts/aerosols. Remove all sources of ignition. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
Wear personal protection equipment.

##### **For non-emergency personnel**

First aider: Pay attention to self-protection!

##### **For emergency responders**

Fight fire with normal precautions from a reasonable distance.

#### **6.2. Environmental precautions**

Do not allow to enter into surface water or drains. Prevent spread over a wide area (e.g. by containment or oil barriers). Ensure all waste water is collected and treated via a waste water treatment plant.

#### **6.3. Methods and material for containment and cleaning up**

##### **For containment**

Prevent spread over a wide area (e.g. by containment or oil barriers).

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### Oktan-Booster 206 - 300 ml

Revision date: 13.01.2026

Product code: 1105024

Page 4 of 13

#### For cleaning up

Clean contaminated articles and floor according to the environmental legislation.

#### Other information

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents). Clean contaminated articles and floor according to the environmental legislation.

#### 6.4. Reference to other sections

Safe handling: see section 7

Personal protection equipment: see section 8

Disposal: see section 13

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

#### Advice on safe handling

Observe instructions for use.

Dust must be exhausted directly at the point of origin. Vapours/aerosols must be exhausted directly at the point of origin. If local exhaust ventilation is not possible or not sufficient, the entire working area should be ventilated by technical means.

When using do not eat, drink, smoke, sniff.

Wear personal protection equipment (refer to section 8).

#### Advice on protection against fire and explosion

Keep away from sources of ignition - No smoking.

#### Advice on general occupational hygiene

Avoid exposure. Wear suitable protective clothing. Draw up and observe skin protection programme.

#### Further information on handling

Avoid contact with skin and eyes.

### 7.2. Conditions for safe storage, including any incompatibilities

#### Requirements for storage rooms and vessels

Keep container tightly closed. Observe legal regulations and provisions.

#### Hints on joint storage

Do not store together with: Oxidizing agents. Pyrophoric or self-heating substances. Food and feedingstuffs.

#### Further information on storage conditions

Store in a cool dry place. Observe legal regulations and provisions.

### 7.3. Specific end use(s)

No information available.

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

#### Occupational exposure limit values

CAS No	Name of agent	ppm	mg/m <sup>3</sup>	fib/cm <sup>3</sup>	Category	Origin
67-56-1	Methanol	200	260		TWA (8 h)	
1634-04-4	Tertiary-butyl-methyl ether	50	183.5		TWA (8 h)	
		100	367		STEL (15 min)	

#### Additional advice on limit values

a no restriction

b End of exposure or end of shift

c at long-term exposure:

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### Oktan-Booster 206 - 300 ml

Revision date: 13.01.2026

Product code: 1105024

Page 5 of 13

d before next shift

blood (B)  
 Urine (U)

#### **8.2. Exposure controls**

##### **Appropriate engineering controls**

If handled uncovered, arrangements with local exhaust ventilation have to be used.

##### **Individual protection measures, such as personal protective equipment**

##### **Eye/face protection**

Suitable eye protection: Tightly sealed safety glasses.  
 EN 166

##### **Hand protection**

Protect skin by using skin protective cream. When handling with chemical substances, protective gloves must be worn with the CE-label including the four control digits. The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances.

Suitable material: NBR (Nitrile rubber) Breakthrough time: 480min  
 Thickness of the glove material 0,45 mm  
 EN ISO 374

##### **Skin protection**

Wear suitable protective clothing. Take off immediately all contaminated clothing and wash it before reuse.

##### **Respiratory protection**

Wear breathing apparatus if exposed to vapours/dusts/aerosols.  
 When exceeding the relevant workplace exposure limits, note the following:  
 Suitable respiratory protective equipment: Combination filter device (DIN EN 141)..  
 Filtering device with filter or ventilator filtering device of type: A  
 Observe the wear time limits as specified by the manufacturer.  
 Observe legal regulations and provisions.

##### **Environmental exposure controls**

Observe legal regulations and provisions.

## SECTION 9: Physical and chemical properties

#### **9.1. Information on basic physical and chemical properties**

Physical state:	Liquid
Colour:	brown
Odour:	solvent like

	<b>Test method</b>
Boiling point or initial boiling point and boiling range:	55 °C
Lower explosion limits:	0,6 vol. %
Upper explosion limits:	8,4 vol. %
Flash point:	-22 °C ISO 3679
Auto-ignition temperature:	> 200 °C
pH-Value (at 20 °C):	DIN 19268
Viscosity / kinematic: (at 40 °C)	< 7 mm <sup>2</sup> /s DIN EN ISO 3104
Density (at 20 °C):	0,753 g/cm <sup>3</sup> DIN 51757

#### **9.2. Other information**

##### **Information with regard to physical hazard classes**

Sustained combustibility: No data available

# Safety Data Sheet

according to Regulation (EC) No 1907/2006

## Oktan-Booster 206 - 300 ml

Revision date: 13.01.2026

Product code: 1105024

Page 6 of 13

### Other safety characteristics

Sublimation point:	No information available.
Softening point:	No information available.
Pour point:	No information available.
Viscosity / dynamic:	DIN 53019-1
Flow time: (at 20 °C)	DIN EN ISO 2431

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

Highly flammable

### 10.2. Chemical stability

The product is stable under normal conditions.

### 10.3. Possibility of hazardous reactions

No hazardous reaction when handled and stored according to provisions.

### 10.4. Conditions to avoid

Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Take precautionary measures against static discharges.

### 10.5. Incompatible materials

Oxidizing agents. Pyrophoric or self-heating substances.

### 10.6. Hazardous decomposition products

Incomplete combustion and thermolysis gases of different toxicity can occur. In the case of hydrocarbonaceous products such as CO, CO<sub>2</sub>, aldehydes and soot. These can be very dangerous if they are inhaled in high concentrations or in enclosed spaces.

### Further information

Do not mix with other chemicals.

## SECTION 11: Toxicological information

### 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

#### Toxicokinetics, metabolism and distribution

There are no data available on the mixture itself.

#### Acute toxicity

Based on available data, the classification criteria are not met.

#### ATEmix calculated

ATE (oral) > 2000 mg/kg; ATE (dermal) > 2000 mg/kg; ATE (inhalation vapour) > 20 mg/l; ATE (inhalation dust/mist) > 5 mg/l

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### Oktan-Booster 206 - 300 ml

Revision date: 13.01.2026

Product code: 1105024

Page 7 of 13

CAS No	Chemical name				
	Exposure route	Dose	Species	Source	Method
64742-48-9	Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, <2% aromatics				
	oral	LD50 > 5000 mg/kg	Rat		
	dermal	LD50 > 5000 mg/kg	Rabbit		
	inhalation (4 h) vapour	LC50 > 4951 mg/l	Rat		
1634-04-4	tert-butyl methyl ether; MTBE; 2-methoxy-2-methylpropane				
	oral	LD50 3866 mg/kg	Rat		
	dermal	LD50 > 2000 mg/kg	Rat		
	inhalation (4 h) vapour	LC50 85 mg/l	Rat		
68608-26-4	Sulfonic acids, petroleum, sodium salts				
	oral	LD50 >5000 mg/kg	Rat		
	dermal	LD50 >5000 mg/kg	Rabbit		
	inhalation (4 h) dust/mist	LC50 >5 mg/l	Rat		
67-56-1	methanol				
	oral	LD50 6000 mg/kg	Monkey	Amer J Ophthalmol 40: 76-83 (cited in DG)	Determination of the acute toxicity of t
	dermal	LD50 17100 mg/kg	Kaninchen		
	inhalation (4 h) vapour	LC50 128,2 mg/l	Rat	Study report (1980)	Study performed according to internal co
	inhalation dust/mist	ATE 0,5 mg/l			

#### Irritation and corrosivity

Skin corrosion/irritation: Causes skin irritation.

Serious eye damage/eye irritation: Based on available data, the classification criteria are not met.

#### Sensitising effects

Based on available data, the classification criteria are not met.

#### Carcinogenic/mutagenic/toxic effects for reproduction

Germ cell mutagenicity: Based on available data, the classification criteria are not met.

Carcinogenicity: Based on available data, the classification criteria are not met.

Reproductive toxicity: Based on available data, the classification criteria are not met.

No indications of human carcinogenicity exist.

No indications of human germ cell mutagenicity exist.

No indications of human reproductive toxicity exist.

#### STOT-single exposure

May cause drowsiness or dizziness. (Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, <2% aromatics)

#### STOT-repeated exposure

Based on available data, the classification criteria are not met.

#### Aspiration hazard

May be fatal if swallowed and enters airways.

# Safety Data Sheet

according to Regulation (EC) No 1907/2006

## Oktan-Booster 206 - 300 ml

Revision date: 13.01.2026

Product code: 1105024

Page 8 of 13

### Information on likely routes of exposure

Ingestion, Inhalation, Skin contact, Eye contact.

Reference to other sections: 2.1, 4.2.

### Specific effects in experiment on an animal

No information available.

### Additional information on tests

The mixture is classified as hazardous according to regulation (EC) No 1272/2008 [CLP].

### 11.2. Information on other hazards

#### Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to humans as no components meets the criteria.

#### Other information

No information available.

## SECTION 12: Ecological information

### 12.1. Toxicity

Harmful to aquatic life with long lasting effects.

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### Oktan-Booster 206 - 300 ml

Revision date: 13.01.2026

Product code: 1105024

Page 9 of 13

CAS No	Chemical name					
	Aquatic toxicity	Dose	[h]   [d]	Species	Source	Method
64742-48-9	Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, <2% aromatics					
	Acute fish toxicity	LC50 >1000 mg/l	96 h	Oncorhynchus mykiss (Rainbow trout)		
	Acute algae toxicity	ErC50 >1000 mg/l	72 h	Pseudokirchneriella subcapitata		
	Acute crustacea toxicity	EC50 >1000 mg/l	48 h	Daphnia magna		
1634-04-4	tert-butyl methyl ether; MTBE; 2-methoxy-2-methylpropane					
	Acute fish toxicity	LC50 672 mg/l	96 h	Oncorhynchus mykiss (Rainbow trout)		
	Acute algae toxicity	ErC50 > 800 mg/l	72 h	Desmodesmus subspicatus		
	Acute crustacea toxicity	EC50 651 mg/l	48 h	Daphnia magna		
68608-26-4	Sulfonic acids, petroleum, sodium salts					
	Acute fish toxicity	LC50 >10000 mg/l	96 h	Oncorhynchus mykiss (Rainbow trout)		
	Acute algae toxicity	ErC50 >1000 mg/l	72 h	Selenastrum capricornutum		
	Acute crustacea toxicity	EC50 >1000 mg/l	48 h	Daphnia magna (Big water flea)		
67-56-1	methanol					
	Acute fish toxicity	LC50 15400 mg/l	96 h	Lepomis macrochirus	Bulletin of Environmental Contamination	other: EPA-660/3-75-00 9, 1975
	Acute algae toxicity	ErC50 ca. 22000 mg/l	96 h	Pseudokirchneriella subcapitata	Ecotoxicology and Environmental Safety 7	OECD Guideline 201
	Acute crustacea toxicity	EC50 > 10000 mg/l	48 h	Daphnia magna	Water Research 23(4): 495-499 (1989)	other: DIN 38412 Teil 11
	Fish toxicity	NOEC 446,7 mg/l	28 d	Pimephales promelas	SAR and QSAR in Environmental Research,	Calculation performed with ECOSAR
	Crustacea toxicity	NOEC 208 mg/l	21 d	Daphnia magna	OECD QSAR Toolbox Report (2013)	Toxicity of the target chemical is predi

#### 12.2. Persistence and degradability

There are no data available on the mixture itself. AOX (mg/l): 0

CAS No	Chemical name					
	Method	Value	d	Source		
	Evaluation					
64742-48-9	Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, <2% aromatics					
	OECD Guideline 301 F	89 %	28	ECHA		
1634-04-4	tert-butyl methyl ether; MTBE; 2-methoxy-2-methylpropane					
	OECD 301 B	2	28	ECHA		
	Not readily biodegradable (according to OECD criteria)					
67-56-1	methanol					
	OECD 301 E	98	28	EVONIK		
	Easily biodegradable (concerning to the criteria of the OECD)					

# Safety Data Sheet

according to Regulation (EC) No 1907/2006

## Oktan-Booster 206 - 300 ml

Revision date: 13.01.2026

Product code: 1105024

Page 10 of 13

### 12.3. Bioaccumulative potential

There are no data available on the mixture itself.

### Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
1634-04-4	tert-butyl methyl ether; MTBE; 2-methoxy-2-methylpropane	0,94
67-56-1	methanol	-0,77

### BCF

CAS No	Chemical name	BCF	Species	Source
67-56-1	methanol	1	Cyprinus carpio	Comparative Biochemi

### 12.4. Mobility in soil

No information available.

### 12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

This substance does not meet the criteria for classification as PBT or vPvB.

### 12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

### 12.7. Other adverse effects

No information available.

### Further information

Do not allow uncontrolled discharge of product into the environment.

## SECTION 13: Disposal considerations

### 13.1. Waste treatment methods

#### **Disposal recommendations**

Do not allow to enter into surface water or drains. Dispose of waste according to applicable legislation.

#### **List of Wastes Code - residues/unused products**

070704 WASTES FROM ORGANIC CHEMICAL PROCESSES; wastes from the MFSU of fine chemicals and chemical products not otherwise specified; other organic solvents, washing liquids and mother liquors; hazardous waste

#### **List of Wastes Code - used product**

070704 WASTES FROM ORGANIC CHEMICAL PROCESSES; wastes from the MFSU of fine chemicals and chemical products not otherwise specified; other organic solvents, washing liquids and mother liquors; hazardous waste

#### **List of Wastes Code - contaminated packaging**

150110 WASTE PACKAGING; ABSORBENTS, WIPING CLOTHS, FILTER MATERIALS AND PROTECTIVE CLOTHING NOT OTHERWISE SPECIFIED; packaging (including separately collected municipal packaging waste); packaging containing residues of or contaminated by hazardous substances; hazardous waste

#### **Contaminated packaging**

Water (with cleaning agent). Completely emptied packages can be recycled.

## SECTION 14: Transport information

### **Land transport (ADR/RID)**

#### 14.1. UN number or ID number:

UN 1993

#### 14.2. UN proper shipping name:

FLAMMABLE LIQUID, N.O.S. (Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, <2% aromatics, tert-butyl methyl ether; MTBE; 2-methoxy-2-methylpropane)

# Safety Data Sheet

according to Regulation (EC) No 1907/2006

## Oktan-Booster 206 - 300 ml

Revision date: 13.01.2026

Product code: 1105024

Page 11 of 13

<b>14.3. Transport hazard class(es):</b>	3
<b>14.4. Packing group:</b>	II
Hazard label:	3
Classification code:	F1
Special Provisions:	274 601 640C
Limited quantity:	1 L
Excepted quantity:	E2
Transport category:	2
Hazard No:	33
Tunnel restriction code:	D/E

### Inland waterways transport (ADN)

<b>14.1. UN number or ID number:</b>	UN 1993
<b>14.2. UN proper shipping name:</b>	FLAMMABLE LIQUID, N.O.S. (Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, <2% aromatics, tert-butyl methyl ether; MTBE; 2-methoxy-2-methylpropane)
<b>14.3. Transport hazard class(es):</b>	3
<b>14.4. Packing group:</b>	II
Hazard label:	3
Classification code:	F1
Special Provisions:	274 601 640C
Limited quantity:	1 L
Excepted quantity:	E2

### Marine transport (IMDG)

<b>14.1. UN number or ID number:</b>	UN 1993
<b>14.2. UN proper shipping name:</b>	FLAMMABLE LIQUID, N.O.S. (Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclenes, <2% aromatics, tert-butyl methyl ether; MTBE; 2-methoxy-2-methylpropane)
<b>14.3. Transport hazard class(es):</b>	3
<b>14.4. Packing group:</b>	II
Hazard label:	3
Marine pollutant:	no
Special Provisions:	274
Limited quantity:	1 L
Excepted quantity:	E2
EmS:	F-E, S-E

### Air transport (ICAO-TI/IATA-DGR)

<b>14.1. UN number or ID number:</b>	UN 1993
<b>14.2. UN proper shipping name:</b>	FLAMMABLE LIQUID, N.O.S. (Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclenes, <2% aromatics, tert-butyl methyl ether; MTBE; 2-methoxy-2-methylpropane)
<b>14.3. Transport hazard class(es):</b>	3
<b>14.4. Packing group:</b>	II
Hazard label:	3
Special Provisions:	A3
Limited quantity Passenger:	1 L
Passenger LQ:	Y341
Excepted quantity:	E2
IATA-packing instructions - Passenger:	353
IATA-max. quantity - Passenger:	5 L
IATA-packing instructions - Cargo:	364
IATA-max. quantity - Cargo:	60 L

### 14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS:	No
----------------------------	----

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### Oktan-Booster 206 - 300 ml

Revision date: 13.01.2026

Product code: 1105024

Page 12 of 13

## SECTION 15: Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### EU regulatory information

Restrictions on use (REACH, annex XVII):

Entry 3, Entry 40, Entry 75

Directive 2010/75/EU on industrial emissions: No information available.

Directive 2004/42/EC on VOC in paints and varnishes: No information available.

#### Additional information

Safety Data Sheet according to Regulation (EC) No. 1907/2006 (REACH)

#### National regulatory information

Water hazard class (D): 1 - slightly hazardous to water

## SECTION 16: Other information

#### Changes

This data sheet contains changes from the previous version in section(s): 16.

#### Abbreviations and acronyms

Flam. Liq: Flammable liquid

Acute Tox: Acute toxicity

Asp. Tox: Aspiration hazard

Skin Irrit: Skin irritation

Eye Irrit: Eye irritation

STOT SE: Specific target organ toxicity - single exposure

Aquatic Chronic: Chronic aquatic hazard

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

IATA: International Air Transport Association

IMDG: International Maritime Code for Dangerous Goods

GHS: Globally Harmonized System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

DNEL/DMEL: Derived No Effect Level / Derived Minimal Effect Level

WEL: Workplace Exposure Limits

TWA (EC): Time-Weighted Average

ATE: Acute Toxicity Estimate

ATEL (EC): Short Term Exposure Limit

LC50: Lethal Concentration

EC50: half maximal Effective Concentration

ErC50: means EC50 in terms of reduction of growth rate

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### Oktan-Booster 206 - 300 ml

Revision date: 13.01.2026

Product code: 1105024

Page 13 of 13

#### Classification for mixtures and used evaluation method according to Regulation (EC) No 1272/2008 [CLP]

Classification	Classification procedure
Flam. Liq. 2; H225	On basis of test data
Skin Irrit. 2; H315	Calculation method
STOT SE 3; H336	Calculation method
Asp. Tox. 1; H304	Calculation method
Aquatic Chronic 3; H412	Calculation method

#### Relevant H and EUH statements (number and full text)

H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H301	Toxic if swallowed.
H304	May be fatal if swallowed and enters airways.
H311	Toxic in contact with skin.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H331	Toxic if inhaled.
H336	May cause drowsiness or dizziness.
H370	Causes damage to organs.
H412	Harmful to aquatic life with long lasting effects.
EUH066	Repeated exposure may cause skin dryness or cracking.

#### Further Information

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

*(The data for the relevant ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)*