Safety Data Sheet

according to Regulation (EC) No 1907/2006

Parts Center DPF Reiniger 400ml

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Parts Center DPF Reiniger 400ml

UFI: QC00-P0GX-7004-GEDJ

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

Cleaner

1.3. Details of the supplier of the safety data sheet

Company name: Parts-Center AG
Street: Heiligwies 16a
Postfach 120
Place: LI-9496 Balzers
Telephone:
E-mail: info@parts-center.ch
Internet: www.parts-center.ch

1.4. Emergency telephone number:

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Regulation (EC) No 1272/2008

Aerosol 3; H229
Skin Irrit. 2; H315
Eye Irrit. 2; H319

Full text of hazard statements: see SECTION 16.

2.2. Label elements

Regulation (EC) No 1272/2008

Signal word: Warning

Pictograms:



Hazard statements

H229	Pressurised container: May burst if heated.
H315	Causes skin irritation.
H319	Causes serious eye irritation.

Precautionary statements

P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P251	Do not pierce or burn, even after use.
P280	Wear protective gloves and eye protection/face protection.
P302+P352	IF ON SKIN: Wash with plenty of water.
P332+P313	If skin irritation occurs: Get medical advice/attention.
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P337+P313	If eye irritation persists: Get medical advice/attention.
P410+P412	Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

Special labelling

2,1 % by mass of the contents are flammable.

2.3. Other hazards

In case of insufficient ventilation and/or through use, explosive/highly flammable mixtures may develop.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Relevant ingredients

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	Classification (Regulation (EC) No 1272/2008)			
141-43-5	2-aminoethanol; ethanolamine			1 - < 3 %
	205-483-3	603-030-00-8	01-2119486455-28	
	Acute Tox. 4, Acute Tox. 4, Acute Tox. 4, Skin Corr. 1B, STOT SE 3, Aquatic Chronic 3; H332 H312 H302 H314 H335 H412			

Full text of H and EUH statements: see section 16.

Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity
	Specific Conc. Limits, M-factors and ATE		
141-43-5	205-483-3	2-aminoethanol; ethanolamine	1 - < 3 %
	inhalation: ATE = 11 mg/l (vapours); inhalation: ATE = 1,5 mg/l (dusts or mists); dermal: LD50 = 1025 mg/kg; oral: LD50 = 1515 mg/kg STOT SE 3; H335: >= 5 - 100		

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

First aider: Pay attention to self-protection! Remove persons to safety. Never give anything by mouth to an unconscious person or a person with cramps.

After inhalation

Remove person to fresh air and keep comfortable for breathing. In all cases of doubt, or when symptoms persist, seek medical advice.

After contact with skin

Wash with plenty of water and soap. Take off immediately all contaminated clothing and wash it before reuse. In all cases of doubt, or when symptoms persist, seek medical advice.

After contact with eyes

Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. In case of troubles or persistent symptoms, consult an ophthalmologist.

After ingestion

Do NOT induce vomiting. Observe risk of aspiration if vomiting occurs. Call a physician in any case!

4.2. Most important symptoms and effects, both acute and delayed

Headache, nausea, dizziness, fatigue, skin irritation

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically. Call a POISON CENTER. Symptoms can occur only after several hours.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Water mist. Foam. Carbon dioxide (CO2). Extinguishing powder.

Unsuitable extinguishing media

Full water jet

5.2. Special hazards arising from the substance or mixture

In case of fire may be liberated: Hazardous combustion products; Pyrolysis products, toxic

5.3. Advice for firefighters

In case of fire and/or explosion do not breathe fumes. Move undamaged containers from immediate hazard area if it can be done safely. In case of fire: Wear self-contained breathing apparatus.

Additional information

Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General advice

Wear breathing apparatus if exposed to vapours/dusts/aerosols. Remove all sources of ignition. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
Wear personal protection equipment.

For non-emergency personnel

First aider: Pay attention to self-protection!

For emergency responders

Fight fire with normal precautions from a reasonable distance.

6.2. Environmental precautions

Do not allow to enter into surface water or drains. Prevent spread over a wide area (e.g. by containment or oil barriers). Ensure all waste water is collected and treated via a waste water treatment plant.

6.3. Methods and material for containment and cleaning up

For containment

Prevent spread over a wide area (e.g. by containment or oil barriers).

For cleaning up

Clean contaminated articles and floor according to the environmental legislation.

Other information

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents). Clean contaminated articles and floor according to the environmental legislation.

6.4. Reference to other sections

Safe handling: see section 7
Personal protection equipment: see section 8
Disposal: see section 13

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Observe instructions for use.
Dust must be exhausted directly at the point of origin. Vapours/aerosols must be exhausted directly at the point of origin. If local exhaust ventilation is not possible or not sufficient, the entire working area should be ventilated by technical means.
When using do not eat, drink, smoke, sniff.
Wear personal protection equipment (refer to section 8).
In case of insufficient ventilation and/or through use, explosive/highly flammable mixtures may develop.

Advice on protection against fire and explosion

Heating causes rise in pressure with risk of bursting.

Advice on general occupational hygiene

Avoid exposure. Wear suitable protective clothing. Draw up and observe skin protection programme.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep container tightly closed. Observe legal regulations and provisions.

Hints on joint storage

Do not store together with: Oxidizing agents. Pyrophoric or self-heating substances. Food and feedingstuffs.

Further information on storage conditions

Protect from frost. Protect from direct sunlight. Store in a cool dry place. Observe legal regulations and provisions.

7.3. Specific end use(s)

No information available.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limit values

CAS No	Name of agent	ppm	mg/m³	fib/cm³	Category	Origin
141-43-5	2-Aminoethanol	1	2.5		TWA (8 h)	
		3	7.6		STEL (15 min)	

DNEL/DMEL values

CAS No	Name of agent		
DNEL type	Exposure route	Effect	Value
141-43-5	2-aminoethanol; ethanolamine		
Worker DNEL, long-term	inhalation	systemic	1 mg/m³
Worker DNEL, long-term	inhalation	local	0,51 mg/m³
Worker DNEL, long-term	dermal	systemic	3 mg/kg bw/day
Consumer DNEL, long-term	inhalation	systemic	0,18 mg/m³
Consumer DNEL, long-term	inhalation	local	0,28 mg/m³
Consumer DNEL, long-term	dermal	systemic	1,5 mg/kg bw/day
Consumer DNEL, long-term	oral	systemic	1,5 mg/kg bw/day

PNEC values

CAS No	Name of agent	
Environmental compartment		Value
141-43-5	2-aminoethanol; ethanolamine	
Freshwater		0,07 mg/l
Freshwater (intermittent releases)		0,028 mg/l
Marine water		0,007 mg/l
Freshwater sediment		0,357 mg/kg
Marine sediment		0,036 mg/kg
Microorganisms in sewage treatment plants (STP)		100 mg/l
Soil		1,29 mg/kg

Additional advice on limit values

a no restriction
b End of exposure or end of shift
c at long-term exposure:
d before next shift

blood (B)
Urine (U)

8.2. Exposure controls

Appropriate engineering controls

If handled uncovered, arrangements with local exhaust ventilation have to be used.

Individual protection measures, such as personal protective equipment

Eye/face protection

Suitable eye protection: Tightly sealed safety glasses.
EN 166

Hand protection

Protect skin by using skin protective cream. When handling with chemical substances, protective gloves must be worn with the CE-label including the four control digits. The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances.
Suitable material: NBR (Nitrile rubber) Breakthrough time: 480min
Thickness of the glove material 0,45 mm
EN ISO 374

Skin protection

Wear suitable protective clothing. Take off immediately all contaminated clothing and wash it before reuse.

Respiratory protection

Wear breathing apparatus if exposed to vapours/dusts/aerosols.
When exceeding the relevant workplace exposure limits, note the following:
Suitable respiratory protective equipment: Combination filter device (DIN EN 141)..
Filtering device with filter or ventilator filtering device of type: A
Observe the wear time limits as specified by the manufacturer.
Observe legal regulations and provisions.

Environmental exposure controls

Observe legal regulations and provisions.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state:	Aerosol
Colour:	pink
Odour:	amine-like

		Test method
Melting point/freezing point:	No information available.	
Boiling point or initial boiling point and boiling range:	100 °C	
Flammability:	No information available.	
Flash point:	> 100 °C	
Auto-ignition temperature:	> 200 °C	
pH-Value (at 20 °C):	10,76	DIN 19268
Water solubility:	highly soluble.	
Partition coefficient n-octanol/water:	No information available.	
Vapour pressure:	No information available.	
Vapour pressure:	No information available.	
Density:	1,01 g/cm³	DIN 51757
Relative vapour density:	No information available.	

9.2. Other information

Information with regard to physical hazard classes

Explosive properties

No information available.

Other safety characteristics

Evaporation rate:	No information available.
Solvent separation test:	No information available.
Solvent content:	No information available.
Solid content:	No information available.
Sublimation point:	No information available.
Softening point:	No information available.
Pour point:	No information available.
	No information available.
Viscosity / dynamic:	not applicable
Flow time:	No information available.

Further Information

Data apply to technical substance: Relative density, Colour, Odour, Viscosity, pH.

SECTION 10: Stability and reactivity

10.1. Reactivity

No hazardous reaction when handled and stored according to provisions.

10.2. Chemical stability

The product is stable under normal conditions.

10.3. Possibility of hazardous reactions

Do not expose to temperatures above 50 °C. Heating causes rise in pressure with risk of bursting.

10.4. Conditions to avoid

Keep away from sources of heat (e.g. hot surfaces), sparks and open flames. Vapours can form explosive mixtures with air. Take precautionary measures against static discharges.

10.5. Incompatible materials

Oxidizing agents. Pyrophoric or self-heating substances.

10.6. Hazardous decomposition products

Incomplete combustion and thermolysis gases of different toxicity can occur . In the case of hydrocarbonaceous products such as CO, CO2, aldehydes and soot. These can be very dangerous if they are inhaled in high concentrations or in enclosed spaces.

Further information

Do not mix with other chemicals.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Toxicocinetics, metabolism and distribution

No information available.

Acute toxicity

Based on available data, the classification criteria are not met.

ATEmix calculated

ATE (oral) > 2000 mg/kg; ATE (dermal) > 2000 mg/kg; ATE (inhalation vapour) > 20 mg/l; ATE (inhalation dust/mist) > 5 mg/l

CAS No	Chemical name					
	Exposure route	Dose		Species	Source	Method
141-43-5	2-aminoethanol; ethanolamine					
	oral	LD50 mg/kg	1515	Rat		
	dermal	LD50 mg/kg	1025	Rabbit	IUCLID	
	inhalation vapour	ATE	11 mg/l			
	inhalation dust/mist	ATE	1,5 mg/l			

Irritation and corrosivity

Skin corrosion/irritation: Causes skin irritation.

Serious eye damage/eye irritation: Causes serious eye irritation.

Sensitising effects

Based on available data, the classification criteria are not met.

Carcinogenic/mutagenic/toxic effects for reproduction

Germ cell mutagenicity: Based on available data, the classification criteria are not met.

Carcinogenicity: Based on available data, the classification criteria are not met.

Reproductive toxicity: Based on available data, the classification criteria are not met.

STOT-single exposure

Based on available data, the classification criteria are not met.

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

Based on available data, the classification criteria are not met.

Information on likely routes of exposure

Ingestion, Inhalation, Skin contact, Eye contact.

Reference to other sections: 2.1, 4.2.

Specific effects in experiment on an animal

No information available.

Additional information on tests

The mixture is classified as hazardous according to regulation (EC) No 1272/2008 [CLP].

11.2. Information on other hazards

Endocrine disrupting properties

Based on available data, the classification criteria are not met.

Other information

No information available.

SECTION 12: Ecological information

12.1. Toxicity

Based on available data, the classification criteria are not met.

CAS No	Chemical name						
	Aquatic toxicity	Dose		[h] | [d]	Species	Source	Method
141-43-5	2-aminoethanol; ethanolamine						
	Acute fish toxicity	LC50	150 mg/l	96 h	Oncorhynchus mykiss	IUCLID	
	Acute algae toxicity	ErC50	22 mg/l	72 h	Desmodesmus subspicatus		
	Acute crustacea toxicity	EC50	65 mg/l	48 h	Daphnia magna		

12.2. Persistence and degradability

There are no data available on the mixture itself. AOX (mg/l): 0

12.3. Bioaccumulative potential

There are no data available on the mixture itself.

Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
141-43-5	2-aminoethanol; ethanolamine	-1,91

12.4. Mobility in soil

No information available.

12.5. Results of PBT and vPvB assessment

Based on available data, the classification criteria are not met.

12.6. Endocrine disrupting properties

Based on available data, the classification criteria are not met.

12.7. Other adverse effects

No information available.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal recommendations

Do not allow to enter into surface water or drains. Dispose of waste according to applicable legislation.

List of Wastes Code - residues/unused products

160504 WASTES NOT OTHERWISE SPECIFIED IN THE LIST; gases in pressure containers and discarded chemicals; gases in pressure containers (including halons) containing hazardous substances; hazardous waste

List of Wastes Code - used product

160504 WASTES NOT OTHERWISE SPECIFIED IN THE LIST; gases in pressure containers and discarded chemicals; gases in pressure containers (including halons) containing hazardous substances; hazardous waste

List of Wastes Code - contaminated packaging

150104 WASTE PACKAGING; ABSORBENTS, WIPING CLOTHS, FILTER MATERIALS AND PROTECTIVE CLOTHING NOT OTHERWISE SPECIFIED; packaging (including separately collected municipal packaging waste); metallic packaging

SECTION 14: Transport information

Land transport (ADR/RID)

14.1. UN number or ID number:	UN 1950
14.2. UN proper shipping name:	AEROSOLS
14.3. Transport hazard class(es):	2
14.4. Packing group:	-
Hazard label:	2.2
Classification code:	5A
Special Provisions:	190 327 344 625
Limited quantity:	1 L
Excepted quantity:	E0
Transport category:	3
Tunnel restriction code:	E

Inland waterways transport (ADN)

14.1. UN number or ID number:	UN 1950
14.2. UN proper shipping name:	AEROSOLS
14.3. Transport hazard class(es):	2
14.4. Packing group:	-
Hazard label:	2.2
Classification code:	5A
Special Provisions:	190 327 344 625
Limited quantity:	1 L
Excepted quantity:	E0

Marine transport (IMDG)

14.1. UN number or ID number:	UN 1950
14.2. UN proper shipping name:	AEROSOLS
14.3. Transport hazard class(es):	2.2
14.4. Packing group:	-
Hazard label:	2.2
Special Provisions:	63, 190, 277, 327, 344, 959
Limited quantity:	1000 mL
Excepted quantity:	E0
EmS:	F-D, S-U

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number or ID number:	UN 1950
14.2. UN proper shipping name:	AEROSOLS
14.3. Transport hazard class(es):	2.2
14.4. Packing group:	-
Hazard label:	2.2
Special Provisions:	A98 A145 A167 A802
Limited quantity Passenger:	30 kg G
Passenger LQ:	Y203

Excepted quantity:	E0
IATA-packing instructions - Passenger:	203
IATA-max. quantity - Passenger:	75 kg
IATA-packing instructions - Cargo:	203
IATA-max. quantity - Cargo:	150 kg

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS:	No
Marine pollutant:	no

14.6. Special precautions for user

No information available.

14.7. Maritime transport in bulk according to IMO instruments

not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulatory information

Restrictions on use (REACH, annex XVII):
Entry 3, Entry 75

Directive 2010/75/EU on industrial emissions:	No information available.
Directive 2004/42/EC on VOC in paints and varnishes:	No information available.

Additional information

Safety Data Sheet according to Regulation (EC) No. 1907/2006 (REACH)
Aerosol Directive (75/324/EEC)

National regulatory information

Water hazard class (D):	1 - slightly hazardous to water

SECTION 16: Other information

Changes

This data sheet contains changes from the previous version in section(s): 11,12.

Abbreviations and acronyms

Aerosol 3: Aerosols, hazard category 3
Acute Tox. 4: Acute toxicity, hazard category 4
Skin Corr. 1B: Skin corrosion, sub-category 1B
Skin Irrit. 2: Skin irritation, hazard category 2
Eye Irrit. 2: Eye irritation, hazard category 2
STOT SE 3: Specific target organ toxicity - single exposure, hazard category 3
Aquatic Chronic 3: Hazardous to the aquatic environment, long-term hazard category: Chronic 3
ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)
RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)
IATA: International Air Transport Association
IMDG: International Maritime Code for Dangerous Goods
GHS: Globally Harmonized System of Classification and Labelling of Chemicals
EINECS: European Inventory of Existing Commercial Chemical Substances
ELINCS: European List of Notified Chemical Substances
CAS: Chemical Abstracts Service (division of the American Chemical Society)
DNEL/DMEL: Derived No Effect Level / Derived Minimal Effect Level
WEL (UK): Workplace Exposure Limits
TWA (EC): Time-Weighted Average
ATE: Acute Toxicity Estimate
STEL (EC) Short Term Exposure Limit
LC50: Lethal Concentration
EC50: half maximal Effective Concentration
ErC50: means EC50 in terms of reduction of growth rate

Classification for mixtures and used evaluation method according to Regulation (EC) No 1272/2008 [CLP]

Classification	Classification procedure
Aerosol 3; H229	On basis of test data
Skin Irrit. 2; H315	Bridging principle "Aerosols"
Eye Irrit. 2; H319	Bridging principle "Aerosols"

Relevant H and EUH statements (number and full text)

H229	Pressurised container: May burst if heated.
H302	Harmful if swallowed.
H312	Harmful in contact with skin.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H412	Harmful to aquatic life with long lasting effects.

Further Information

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

(The data for the relevant ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)